TOSHIBA

B-SX8T INDUSTRIAL PRINTER

Product brochure

- The B-SX8 industrial printer from Toshiba with powerful networking delivers outstanding performance for a wide variety of environments and applications.
- This innovative printer offers advanced features including extremely fast processing, large internal memory, web printer controls and outstanding SNMP networking tools.





KEY HIGHLIGHTS

- Advanced connectivity features
- Increased expandability options
- Higher processing speed to improve data processing of large files
- > Easy maintenance and low cost of ownership



APPLICATIONS

The Toshiba B-SX8 printer with the ultimate in networking tools is ideal for for a large range of applications:

- Logistics
- Shipping/Receiving label, address label, contana label
- Manufacturing
 - Carton label, Rating label, Picking label, Parts label
- > Other Industries
 - e.g. Automotive, Paper, Chemical, Pharmaceutical, Textile

WITH PEACE OF MIND BUILT IN

Speed and Functionality

Utilising field-proven CPU technology from Toshiba the B-SX8 model offers high-speed printing and enhanced processing via an extensive choice of interfaces - including USB and internal LAN. The options of serial and wireless LAN interfaces provide additional flexibility and choice, making this printer adaptable to the widest variety of environments and applications.

High Print Quality

The high-resolution, wide print head of the B-SX8 facilitate speedy printing of large format compliance labels. A floating print head mechanism guarantees superb print quality with reduced friction and a flat paper path. The standard ribbon save function conserves the ribbon when it is not required, reducing costs and the amount of down-time required for ribbon changing.

Future Proofing

For future proofing, the B-SX8 printer is compatible with legacy systems. With the powerful Basic Command Interpreter (BCI) program, incoming data can be manipulated to generate the correct label formats. The BCI can also communicate with external devices allowing the easy integration of other technology systems.

SNMP Tools

The B-SX8 comes with a free Central Network Management Suite that allows the user to:

- Manage all the Toshiba printers attached to the network through their IP address.
- Exhibit system information and firmware versions, allowing firmware to be updated across the network simultaneously.
- View the status of each individual printer connected to the network in real-time with real-time alerts; including viewing web pages.
- View a graphical display of the alerted error with instructions on the actions necessary to resolve it.

Lower Cost of Ownership

This Toshiba product is manufactured at Toshiba's own facilities providing the assurance of complete reliability and quality of key components essential for low overall cost of ownership (TCO). To further lower the TCO the B-SX8 printer has large internal memory as standard with no requirement for additions! memory.

SPECIFICATIONS

General

Print Method Thermal transfer/Direct thermal

Printhead Egde type

Dimensions (W x D x H) 416 x 289 x 395 mm

Weight 25 kg

Memory 16 MB (FROM), 16 MB (SRAM)

User interface 2 line LCD (16 characters), 3 x LED, 3 x key

Operating Temperature /

Humidity

 5°C to 40°C / 25--85% non-condensing

relative humidity (RH)

Storage Temperature /

-40°C to 60°C / 10-90% non-condensing

Humidity relative humidity (RH)

Power Supply AC 100 to 240 V, 50/60 Hz

Print

 Resolution
 305 dpi (12 dots/mm)

 Sensor
 Reflective, Transmissible

 Maximum Print Speed
 203 mm/second (8 ips)

Maximum Print Width 213.3 mm

Maximum Print Length Batch: 8-1,364 mm

Cut: 23-1,364 mm Peel-off:20.9-1,364 mm

Barcodes UPC/EAN/JAN, Code 39, Code 93, Code 128,

EAN 128, NW7, MSI, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, Postnet, RM4SCC, KIX-Code,

GS1 Databa

2D Codes Data Matrix, PDF 417, Maxicode, QR Code,

Micro PDF 417, CP Code

Fonts Bitmap font, Outline font, Price font, TTF, Writable

characters

Media

Alignment Centred

Backing Paper Width 101.6 - 225 mm

Label Thickness 0.13-0.17 mm

Tag Thickness 0.10-0.17 mm

Inner Media Core Diameter 76 mm

Outer Media Roll Diameter 203 mm

Media Type Vellum paper and labels, Matt coated paper,

Glossy coated paper, Synthetic film, PET film,

Polyimide

Media Format Roll, Fanfold

Software & Connectivity

Printer Driver Windows 10/8/7/Vista (32/64 bit),

Windows Server 2012/Server 2008 (32/64 bit)

Interface Parallel port, USB 2.0, LAN (10/100Base), Serial port¹⁾,

Expansion I/O1)

Language Mode TPCL, BCI (function)

Label Software BarTender UltraLite

Options

Cutter module, Strip module, Serial interface board, Expansion I/O board, RTC

(real time clock)

1) Optional



Ribbon

Ribbon Width 115-224 mm
Ribbon Core Size 25.4 mm (1 inch)

Fixed Core Length 228 mm

Max. Ribbon Length 300 m

Max. Ribbon Diameter 72 mm



About Toshiba Tec

Toshiba Tec Malaysia Sdn. Bhd. is part of the globally operating Toshiba Tec Corporation, active in various high-tech industrial sectors.

Toshiba Tec Corporation is a leading provider of information technology, operating across multiple industries – ranging from retail, education and business services to hospitality and manufacturing. With headquarters in Japan and over 80 subsidiaries worldwide, Toshiba Tec Corporation helps organisations transform the way they create, record, share, manage and display information.

For more information please contact us:

Toshiba Tec (Thailand) Co., Ltd. (0105547146144)

No.43, Thai CC Tower, Room 164-166, 16th Floor South Sathorn Road, Yannawa, Sathorn, Bangkok 10120 Thailand.

Tel:+662-672-3728 Service:+662-672-3728 Fax:+662-672-3730

Website: www.toshibatec.co.th

Distributed by		
	┐	Together Information is Toshiba's vision for how people and organisatio create, record, share, manage and display ideas and data.
		It is based on our belief that the most successful organisations are those that communicate information in the most efficient way.
		We make that possible through an integrated portfolio of industry-specific solutions, all of which reflect Toshiba's commitment t the future of the planet.
I	1	
	_	