

B-FP3D-GH MOBILE PRINTER

Datasheet

- > Expand the potential of your mobile workforce, with Toshiba's compact and rugged range of mobile 3 inch label printers.
- > Focusing on label printing including price mark-down, shelf labelling, shipping labelling and others, the powerful system architecture enhances the printer's performance whilst future-proofing your investment.
- > Designed for the ultimate user experience, with easy operation and the flexibility to operate in the most diverse working environments.



Ready when you are!

Market leading print speeds of up to 6 inches per second, faster processing with an advanced CPU and a rapid boot time, guarantee the B-FP3D is ready to print, labels and receipts quickly and efficiently at the touch of a button. A long-life, powerful battery offers extended operational time to keep your business moving — and minimise down-time.

Simple to use

Small & light, easy to handle, the B-FP3D has been designed with the user in-mind. Simple to operate with a full colour graphical LCD display, providing easily visible status updates. Drop in, large capacity media loading, for quick and efficient media changes and a double tear-off bar for operator flexibility.

SPECIFICATIONS

Models

B-FP3D-GH30-QM-R / B-FP3D-GH30-CN-R
(Interface: Bluetooth)

B-FP3D-GH40-QM-R / B-FP3D-GH40-CN-R
(Interface: Wireless LAN)

B-FP3D-GH52-QM-R
(Interface: Bluetooth + Wireless LAN)

* The models vary depending on sales regions or interface.

General

Print Method	Direct thermal
Printhead	Flat head
Dimensions (W x D x H)	116 x 150 x 80 mm
Weight	660 g (with Battery)
Memory	64 MB (FROM), 32 MB (SRAM)
Durability	1.6 m (multiple drops to concrete)
IP54 compliant	yes, excluding the paper path
User Interface	128 x 128 pixel Graphic Colour Display 2 x LED (colours: green, amber, red), 3 x key
Operating Temperature / Humidity	-15°C - 50°C (5°F - 122°F), 25-85% non-condensing relative humidity (RH)
Charging Temperature / Humidity	0°C - 40°C (32°F - 104°F), 25-85% non-condensing relative humidity (RH)
Battery	Lithium ion 7.4V, 2500 mAh

Print

Resolution	203 dpi (8 dots/mm)
Sensor	Reflective, Transmissible
Maximum Print Speed	152 mm/second (6 ips)
Maximum Print Width	72 mm
Print Length	Batch: 5 - 995 mm Receipts with black mark: 5 - 995 mm Peel-off: 8 - 58 mm
Barcodes	UPC/EAN/JAN, Code 39, Code 93, Code 128, EAN 128, NW7, MSI, Interleaved 2 of 5, Industrial 2 of 5, Postnet, RM4SCC, KIX-Code, GS1 Databar, Plessey
2D Codes	Data Matrix, PDF 417, Maxicode, QR Code, Micro PDF 417, Micro QR, GS1 Data Matrix
Fonts	Bitmap font, Outline font, Price font, TTF, OTF, Writable characters

Media

Alignment	Centred
Backing Paper Width	Label: 26 - 80 mm
Inner Media Core Diameter	12 mm
Outer media Roll Diameter	68 mm
Media Type	Label, receipt, tag
Issue Mode	Batch, Peel-off

Software & Connectivity

Emulation	ZPL II, SPBL, CPCL
Printer Driver	Windows 10/8.1/8/7 (32/64 bit), Windows Server 2016, Windows Server 2012 R2/Server 2012, Windows Server 2008 R2, SAP, OPOS, JPOS
SDK	iOS, Android, Windows CE
Interface	USB 2.0 Full Speed, Bluetooth v2.1+EDR, v4.0 BLE Dual or Wireless LAN (802.11 a/b/g/n) ¹⁾
Language Mode	TPCL, LABEL, RECEIPT, ESC/POS, Basic Command Interpreter (BCI)
Label Software	BarTender UltraLite (co-packed)

Options

¹⁾ Optional	1-slot battery charger, 6-slot battery charger AC adapter Cigarette lighter adapter DC Jack plug adapter Spare Battery for GH Model Shoulder strap
------------------------	---

¹⁾ Availability varies from country to country

For more information please contact us:

Toshiba Tec Malaysia Sdn. Bhd.

Registration No.: 198101000677 (66785-D)

4, Jalan Saudagar U1/16, Seksyen U1,
Hicom Glenmarie Industrial Park, 40150, Shah Alam,
Selangor Darul Ehsan, Malaysia.

(P.O. Box 7722, Pejabat Pos Besar,
40724 Shah Alam, Selangor Darul Ehsan, Malaysia.)

Tel : +603-5568 7788 Service : +603-5568 7699

Fax : +603-5568 7700

Website : www.toshibatec.com.my

