

Intelligent MFP that meets today's challenging business requirements

- > Colour Multifunction Printer
- > Up to 40 PPM
- > Small Workgroup
- > Copy, Print, Scan, Fax
- > Secure MFP
- Solutions Ready



CONNECT. INTEGRATE. SIMPLIFY. AND MORE.

Technology for every workplace, delivering advanced functionality, ease of use and peace of mind.

Every business is unique. That's why Toshiba offers the latest customisable solutions that can be tailored to meet your needs. Toshiba solutions help you simplify complex tasks while managing diverse information—efficiently and safely to maximise your productivity.

Toshiba's latest series delivers on our promise of Together Information—our commitment to collaborate with clients to provide tailored, cost-effective solutions that meet your print, document management and content needs while helping you to meet your green objectives.

- > Fast 33/40 ppm colour multifunction printer
- Compact all-in-one with copy/print/scan & optional fax capabilities
- > Large 10.1" customisable touch panel
- Smart mobile & cloud connectivity that provide easy access to your document
- > Wide and flexible variety of choice on paper drawers that will suit our demanding needs
- > Small & compact in size that is suitable for
- department use or counter service use
- Toshiba's secure hardisk help safeguard your data integrity

Customisable user interface streamlines complicated multi-step processes into automated one-touch functions.

A fully-customisable user interface with an open platform enables departments to tailor settings and automate workflow including the integration of third-party solutions resulting in simple operation and improved efficiency. Let Toshiba place productivity and performance at your fingertips.

- Customise and automate workflow specifically around your business processes
- Boost productivity by reducing manual and paper intensive processes in the office
- Personalise the user interface by department or individually to deliver the utmost efficiency
- Cost savings and greater efficiency through improved workflow and productivity



Simple, smart and stylish.

A customisable 10.1" tablet-style touch screen with an embedded web browser is easy to use, and customisable to meet your needs, enhancing the sleek and modern look of the complete series.





A COMPACT DESIGN THAT LEAVES NOTHING OUT

Even with a relatively small footprint, the e-STUDIO400AC Series is packed with industryleading technologies and innovations designed to help workgroups connect, integrate and simplify.

High Speeds include 33/40 PPM colours multifunction printer

Advanced e-BRIDGE Next Technology enables the MFP to drive Toshiba's internally developed solutions or those from a third party with ease

Dual-Scan Document Feeder holds an amazing 300 originals and boasts an impressive 240 images per minute (IPM) by scanning both sides of the page in a single pass. e-Suite allows you to track and control copy, fax and scan jobs, and perform secure print release at Toshiba MFP.

Multi-Station Print Enabler allows you to retrieve your print job from a series of networked MFPs – now with support of up to 50 e-BRIDGE devices.

S can and Fax Preview allows you to receive your scanned documents digitally and also view received faxes prior to sending or printing.



COMPACT SIZE FITS IN SMALL SPACES

Perfect fit in organisations looking for device fleet optimisation.

With functionality of an A3 device, e-Studio330AC/400AC can easily integrate into smaller offices and departments that requires lighter output, achieving cost and operation efficiencies

C-STUDIO330AC/400AC

Main Specifications

| - | |
|--------------------|--------------------------------------------------------------------|
| Copy System | Indirect electrostatic photographic method |
| Display | 10.1" LCD touch-screen resistive type |
| Copy Speed | 33 / 40 cpm (A4) |
| | 27 / 33 cpm (B4) |
| First Copy Out | 330AC: 5.7 seconds (mono) / 7.2 seconds (colour) (300 dpi scan) |
| | 400AC: 5.1 seconds (mono) / 6.3 seconds (colour) (300 dpi scan) |
| Warm-Up Time | After Powering On: Approx. 20 seconds |
| Warm-op mile | From Sleep Mode: 18 seconds (e-S330AC) / 18 seconds (e-S400AC) |
| | From Low-power Mode: 18 seconds (e-5330AC) / 18 seconds (e-5400AC) |
| | |
| Stack Feed Bypass | A4 / 52 - 256 gsm / Banner (215.9 x 1320.8 mm) / 90 - 163 gsm |
| Multiple Copying | Up to 999 copies |
| Paper Capacity | Standard Drawer x 1: 550 sheets x 1 |
| | Standard Stack Feed Bypass: 100 sheets |
| | Optional Paper Feed Unit (PFU): 550 sheets |
| | Optional LCF (Pedestal Type): 2,000 sheets |
| Original Feed | 100 - Sheet DSDF |
| Feeding Speed | 58 (A4) |
| Max. Original Size | A4 / Legal |
| Paper Feed Sizes | Drawer 1: 550 Sheets A4 to A5 |
| | Stack Feed Bypass: 100 Sheets - A4 - 98 mm x 148 mm, Legal, Banner |
| Paper Weights | Standard: 550 Sheets - 60 - 256 gsm |
| | Stack Feed Bypass: 100 Sheets - 52 - 256 gsm |
| Duplex | A4 - A5 / 60 - 256 gsm |
| Reproduction Ratio | 25% to 400% |
| Weight | Approx. 53 kg |
| Approx. Dimensions | 520 mm (W) x 540 mm (D) x 634 mm (H) |
| Power Source | 220 - 240 Volts, 50 / 60 Hz, 12 Amps |
| Power Consumption | Max. 2.0kW (220 - 240V) |
| i ower consumption | Super sleep: 0.7W |
| CPU | Intel Apollo Lake E3930 (Dual Core) |
| Memory | |
| | 4 GB (Main memory + Page memory) |
| Hard Disk Drive | 320 GB Toshiba Secure HDD |

e-BRIDGE Next Print Specifications

| PDL | PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| Print Speed | 33 / 33 / 40 / 40 cpm (A4 size) (Mono/ Colour) |
| Print Resolution | 600 dpi x 600 dpi, 3bit (All PDL) |
| | 1,200 dpi x 1,200 dpi, 1bit (PS Driver) |
| Operating Systems | Windows [®] 8.1,10, Windows Server [®] 2012 / R2, Windows Server [®] 2016, |
| 5 | Windows Server [®] 2019, Macintosh [®] (MacOS X 10.6.8, 10.7.4, 10.8, 10.9, |
| | 10.10, 10.11, 10.12, 10.13 10.14), Unix [*] , Linux [*] |
| Network Protocols | TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX* for Novell* Environments, |
| | EtherTalk for Macintosh Environments |
| Interface | RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-speed) |
| | Optional IEEE802.11b/g/n, Optional Bluetooth |
| Mobile Service | AirPrint [®] , Mopria [®] , e-BRIDGE Print & Capture Application on iOS and Android |
| | (Available via Apple [*] App Store or Google Play) |
| Device Management | TopAccess, e-Suite |
| Account Control | Up to 10,000 users or 1,000 Departments Supports User Authentication |
| | (on Device), Login Name/Password (via Windows* domain) or Login Name/ |
| | Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function |
| Security Features | User Authentication, On-Board Data Scramble Function, SCEP, Disable e-Filing, |
| - | Disable Copy, Disk Overwrite, IP Address Filtering (10 Sets), MAC Address Filtering |
| | (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, |
| | SSL/TLS (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS, SYSLOG), IPsec (IKEv1, IKEv2), |
| | Security Mode Change, CC Certified (ISO/IEC15408)* IEEE802.1X (Wired/Wireless), |
| | Digital Signature for Client Utilities, Password Policy, Password Lock, Password |
| | Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, |
| | Security Stamp, Role Based Access Control, Secure PDF, Digital Signature for |
| | firmware update, Integrity Check function, Image Log, Card Authentication, NFC |
| | Authentication |
| | *Conformance with HCD-PPv1.0 in High security mode. |
| Certification | WHQL (Windows [*] 7, 8, 8.1, 10, 2008 R2, 2012, 2012 R2), Novell [*] , Citrix [*] , SAP, AirPrint [*] |
| | and Mopria® |
| | |

Scan Specifications

| Monochrome: 58/116 SPM | | |
|------------------------------------------------------------------------------|--|--|
| Colour: 40/80 SPM (300 dpi), 20/40 SPM (400 dpi, 600 dpi) | | |
| Standard: Full Colour, Auto Colour, Monochrome, Grayscale | | |
| 600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi | | |
| Monochrome: TIFF-Multi / Single Page, PDF-Multi / Single Page, | | |
| Searchable PDF (Opt.), XPS-Multi / Single Page, DOCX (Opt.), | | |
| XLSX (Opt.), PPTX (Opt.) | | |
| Colour / Grayscale: JPEG, TIFF-Multi / Single Page, PDF-Multi / Single Page, | | |
| Slim PDF, Searchable PDF (Opt.), XPS-Multi / Single Page, DOCX (Opt.), | | |
| XLSX (Opt.), PPTX (Opt.) | | |
| Colour / Grayscale: JPEG (High, Middle, Low) | | |
| | | |

Facsimile Specifications

| Compatibility | Super G3, G3 |
|---------------------|-------------------------------------------------------------------|
| Data Compression | JBIG, MMR, MR, MH |
| Transmission Speed | Approx. 3 Seconds Per Page |
| Fax Modem Speed | 33.6kbps2.4Kbps (automatic fall-back) |
| Memory Transmission | 100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations/Job |
| Scan Speed | 0.7 Seconds Per Page, Maximum 73 IPM |

Accessories (Options)

| Paper Handling Options | |
|-----------------------------------------------------|--------------|
| Paper Feed Unit (550 sheets) | MY-1050 |
| Large Capacity Feeder (2,000 sheets) | KD-1071 |
| Spacer | GR-1380 |
| Caster | GR-1390 |
| Offline Stapler | MJ-1047 |
| Staple Cartridge for offline stapler | Stapler-3700 |
| Desk | MH-330AC |
| System Options / Accessories | |
| FAX Unit | GD-1370EU |
| Wireless LAN / Bluetooth Module | GN-4030 |
| Harness kit for coin controller | GQ-1280-N |
| Card Reader Holder | GR-1400 |
| Panel Ten Key Option | GR-1340 |
| FIPS HDD Option | GE-1230 |
| License Enabler Options | |
| Data Overwrite enabler (license) | GP-1070Node |
| Meta scan enabler | GS-1010Node |
| IPSec enabler | GP-1080Node |
| Unicode Font enabler | GS-1007Node |
| Embedded OCR enabler (license) | GS-1080Node |
| Multi Station Print (license) | GP-1090Node |
| IP Fax License | GS-1100Node |
| Hardcopy Security Kit | GP-1190Node |
| e-BRIDGE Plus for Zone OCR V3.0 (Node) | GB-2330Node |
| e-BRIDGE Plus for OneDrive for Business V3.0 (Node) | GB-2300Node |
| e-BRIDGE Plus for SharePoint Online V3.0 (Node) | GB-2310Node |
| e-BRIDGE Plus for Exchange Online V3.0 (Node) | GB-2320Node |
| e-BRIDGE Plus for Gmail (Node) | GB-2380Node |
| e-BRIDGE Plus for G Suite Google Drive (Node) | GB-2390Node |
| Other Options | |
| Accessible Arm | KK-2560 |
| | |



mopria

Toshiba Tec Malaysia Sdn. Bhd. Registration No.: 198101000677 (66785-D)

4, Jalan Saudagar U1/16, Seksyen U1, Hicom Glenmarie Industrial Park, 40150, Shah Alam, Selangor Darul Ehsan, Malaysia. (P.O. Box 7722, Pejabat Pos Besar. 40724 Shah Alam, Selangor Darul Ehsan, Malaysia.) Tel : +603-5568 7788 Service : +603-5568 7699 Fax : +603-5568 7700 Website : www.toshibatec.com.my Distributed by

Technical data is subject to change without prior notice. All company and/or product names are trademarks and/ or registered trademarks of their respective manufacturers in their markets and/or countries. All rights reserved. We are constantly making efforts to deliver the latest status of data to our partners. Specifications for some models may change in the time between the production and the release of this documentation. Productivity and paper specifications are related to paper size of A4 and a paper weight of 80 g/m2 if not otherwise mentioned. **Copyright ©2020 TOSHIBA TEC.**