

TOSHIBA

e-STUDIO2303A

e-STUDIO2303AM

e-STUDIO2803AM

e-STUDIO2309A

e-STUDIO2809A

**Compact.
Efficient.
Economical.**



COPY



PRINT



A3



DUPLEX



**COLOUR
SCAN**



**COPY
SPEED**



**TOGETHER
INFORMATION**

Increased productivity

Offers a wide range of paper handling options to satisfy the varying needs of users.



Colour Scan and Scan to USB

Besides having the capability of Colour Scan, users can also enjoy the convenience of scanning directly to USB drive.



Department codes

Administrators can manage printing cost by tracking the print volume of departments and users, limiting unauthorised usage through this simple security management.



Mobile Printing

Printing is even more hassle-free now! Simply connect and print directly from your mobile phone or tablet.

*With PS option on e-STUDIO2309A/2809A



SPECIFICATION for		e-STUDIO2303A	e-STUDIO2303AM/2803AM	e-STUDIO2309A/2809A
GENERAL				
Copying/Printing Process		Indirect electrostatic photographic method		
Print & Copy Speed		23cpm	23/28cpm	
Warm-up Time		Approx.18 seconds		
Paper Size & Weight		Drawer: A3/A5-R (64 - 80gsm) Stack Feed Bypass: A3/A5-R (52 - 216gsm)		
Paper Capacity		Drawer: 250 sheets Stack Feed Bypass: 100 sheets		
Max. Paper Capacity		600 sheets	1700 sheets	
Paper Exit		Face down/Inner exit (100 sheets)		
Processor		ARM9 360MHz	Cortex A8 500MHz	
Memory		512MB		
Dimensions		W575 x D540 x H402 (mm)		
Weight (Approx.)		27kg		
Power Consumption		1.5kW (220-240V)		
Operation Noise		64.75dB[A]		
Special Features		Auto Sleep Mode, Auto Energy Saver		
COPY				
Max. Original Size		A3		
Resolution		2400dpi x 600dpi (with smoothing)		
Multiple Copy Qty		1-999/Ten key input		
First Copy		Less than 6.4 seconds (A4 size from 1st drawer, 100%)		
Zoom		25% to 400% (1% Increment)		
Copy Mode		Text, Text/Photo(Default), Photo, Background Erase		
Image Density Control		Automatic / Manual (9 Steps)		
PRINT				
Resolution		2400dpi x 600dpi (with smoothing)		
Page Description Language		GDI	PCL6 (PCL,XL), PCL5e, PCL5c, PS (Option)	
Operating Systems		Windows Vista SP2 (32/64 bit) Windows 7 SP1 (32/64 bit) (SP1 Recommended) Windows 8/8.1 (32/64 bit) Windows Server 2008 SP2 (32/64 bit) Windows Server 2008 R2 SP1 (64 bit) Windows Server 2012/R2 (64 bit)		
		N/A	Mac OS 10.6, 10.7.4, 10.8, 10.9, 10.10 UNIX, Linux (CUPS)	
Interface		USB 2.0/Hi Speed	10/100 BaseT, USB 2.0/Hi Speed	
Network Protocol		N/A	TCP/IP (IP v4/IP v6) NetBIOS over TCP/IP	
Print Protocol		N/A	LPR/LPD, Po t 9100 (bi-directional), IPP ver1.1	
Print Function		Toner Save Mode, Watermark, Multiple Pages Per Sheet		
SCAN				
Resolution		600 x 600dpi		
Scan Speed		Up to 25spm		
Scan Modes		B&W, Greyscale, Colour		
File Formats		B&W: TIFF-Multi/Single page, PDF-Multi/Single-Page Greyscale : JPEG, TIFF-Multi/Single page, PDF-Multi/Single Page Colour: JPEG, TIFF-Multi/Single page, PDF-Multi/Single Page		
Scan Agent		Scan to USB, Remote TWAIN		Scan to USB, Remote TWAIN, Scan to File (SMB/FTP), Scan to Email
FAX (OPTION)				
Compatibility		N/A	Super G3, G3	
Data Compression Method		N/A	JBIG, MMR, MR, MH	
Modem Speed		N/A	33.6kbps ~ 2.4Kbps (Auto fallback)	
Transmission Speed		N/A	Approx. 3 sec.	
Broadcast Transmission		N/A	Max. 32 Groups, 220 destinations per job	
OPTIONS				
Document Feeder (RADF)	MR-3029	✓		
Platen Cover	KA-2507PC	✓		
Paper Feed Unit	MY-1043	✓		
Desk	MH-2506	✓		
Harness Kit for Coin Controller	GG-1131	✓		
Auto Duplex Unit	MD-0107	✓		
Paper Feed Pedestal	KD-1039	N.A		N.A (Standard)
Drawer Module	MY-1044	N.A		✓
FAX Kit	GD-1360	N.A		✓
Wireless LAN Module	GN-1080	N.A		✓
PS module + 1GB memory (es2309A)	GA-1340L	N.A		✓
PS module + 1GB memory (es2809A)	GA-1340H	N.A		✓

Distributed by

Microsoft and Windows® are registered trademarks of Microsoft Corporation in the United States and/or other countries. All other brand and/or product names are trademarks of their respective owners. This brochure was compiled based on information that was accurate prior to product launch. Product design and specifications are subject to change without notice. The colour(s) of the actual product may vary from the colour(s) shown in this brochure. No part of this material may be used or reproduced in any manner whatsoever without permission. 1GB is equivalent to 1 billion bytes. Warm-up time and print speed may vary depending on the operating environment. ©2015 TOSHIBA TEC CORPORATION All rights reserved.

TOSHIBA

Toshiba Tec Malaysia Sdn. Bhd. (66785- D)

4, Jalan Saudagar U1/16, Seksyen U1, Hicom Glenmarie Industrial Park,
40150 Shah Alam, Selangor Darul Ehsan, Malaysia.
Tel : 03-5568 7373 Service Hotline : 03-5568 7699 Fax : 03-5568 7992
Website: www.toshibatec.com.my