TOSHIBA

E-STUDIO2329A/2829A

Compact. Efficient. Functional.













COPY SPEED



Enchanced without compromise

Offers enhancements on operability, usability and environmental regulations without the compromise of size and speed.



ID Card Copying

Conveniently copy both sides of an ID card-sized document for improved productivity!

Email Notifications

Notifications via email will be directly sent to an indicated address when a change of toner cartridge is needed!

Mobile Scan/Print

Printing is even more hassle-free now! Simply connect and print or scan directly from your mobile phone!

*Available on Android OS only









SPECIFICATION for		
		e-STUDI02329A/2829A
GENERAL ———		
Copying/Printing Process	3	Indirect electrostatic photographic method
Print & Copy Speed		23/28cpm (A4)/14cpm (A3)
Warm-up Time Paper Size & Weight		Approx.15 seconds Drawer: A3/A5-R (64 - 80qsm)
Paper Size & Weight		Drawer: A3/A5-H (04 - 80g8m) Stack Feed Bypass: A3/A5-H (52 - 216gsm)
Paper Capacity		Drawer: 250 sheets
Max. Paper Capacity		Stack Feed Bypass: 100 sheets 1700 sheets
Paper Exit		1700 streets Face down/Inner exit (100 sheets)
Processor		Cortex A8 500MHz
Memory		512MB / 1GB (Opt. PS option)
Dimensions		W575 x D540 x H402 (mm)
Control Panel		LCD - W66 x H35 (mm) with Back light and Key top
Weight (Approx.)		27kg
Power Consumption		Max. 1.5kW (220 - 240V)
Operation Noise		64.75dB[A]
Special Features		Auto Power Save, Auto Sleep Mode, Energy Saver
COPY —		
Max. Original Size		A3
Resolution		2400dpi x 600dpi (with smoothing)
Multiple Copy Qty		1-999/Fen key input
First Copy		Less than 6.4 seconds (A4 size from 1st drawer, 100%)
Zoom		25% to 400% (1% Increment)
Copy Mode		Text, Text/Photo(Default), Photo, Background Erase
Image Density Control		Automatic / Manual (9 Steps)
DDINT		
PRINT		
Resolution Page Description Language		2400dpi x 600dpi (with smoothing), 600dpi x 600dpi (1 bit)
		PCLSe/ PCLSc/ PCL6 (PCL XL)/ PS3 Emulation (Opt.)
Operating Systems		Windows 7 SP1 (32/64 bit) (SP1 Recommended)
		Windows 8.1 (32/64 bit)
		Windows 10
		Redstone 5 Windows Server 2008 SP2 (32/64 bit)
		Windows Server 2008 IZ 527 (42 bit) Windows Server 2008 IZ 527 (42 bit)
		Windows Server 2012/R2 (64 bit)
		Windows Server 2016
		Mac OS 10.11, 10.12, 10.13, 10.14
		Linux / Redhat Enterprise 5.10.x, 6.5.x, 7.4X / Fedora Version 27 / Open SuSE Leap 42.3 / Bharat Operating System 6.x
Interface		RJ45/USB 2.0
Network Protocol		TCP/IP (IP v4/IP v6) NetBIOS over TCP/IP
Print Protocol		LPR/LPD, Port 9100 (bi-directional), IPP ver1.1
Print Function		Toner Save Mode, Watermark, Multiple Pages Per Sheet
Mobile Print		App (eBPC Entry), USB Connection
		- W
SCAN —		
Resolution		Up to 600 x 600dpi
Scan Speed		Up to 25spm
Scan Modes		B&W, Greyscale, Colour
File Formats		B&W: TIFF-Multi/Single page, PDF-Multi/Single-Page
		Greyscale : JPEG, TIFF-Multi/Single page, PDF-Multi/Single Page
		Colour: JPEG, TIFF-Multi/Single page, PDF-Multi/Single Page
Destination Support		File Server, SMB, FTP, Scan to File, Scan to Email
		Scan to USB/TWAIN
FAX —		
Compatibility		Super G3, G3
Data Compression Method		Sulper US, US BIBG, MMR, MR, MH
Modem Speed		33.6kbps - 24kbps (Auto Fallback)
Transmission Speed		33.00ups = 2.4mups (vita i aliabets) Approx. 3 sec.
Broadcast Transmission		Max. 256 jobs, 220 destinations/job, Max. 384 pages/file
OPTIONS —		
Document Feeder (RADF)	MR-3032	V
Platen Cover	KA-2507PC	V
Paper Feed Unit	MY-1043-B	<u> </u>
Desk Hanness Vit for	MH-2506	<u> </u>
Harness Kit for Coin Controller	GQ-1131	✓
Auto Duplex Unit	MD-0107	N.A (Standard)
Paper Feed Pedestal	KD-1039-B	· ref (contraine)
Drawer Module	MY-1044-B	v
FAX Kit	GD-1380	Ÿ
Wireless LAN Module	GN-1160	·
PS module + 1GB memory	GA-1350L	<u> </u>
(es2329A)	<u> </u>	
PS module + 1GB memory (es2829A)	GA-1350H	Distributed b

Distributed by

Microsoft and Windows* are registered trademarks of Microsoft Corporation in the United States and or other countries. All other brand and/or product names are trademarks of their respective owners. This brochure was compiled based on information that was accurate prior to product launch. Product design an specifications are subject to change without notice. The colour(s) of the actual product may vary from the colour(s) shown in this brochure. No part of this material may be used or reproduced in any manner whatsoever without permission. 1GB is equivalent to 1 billion bytes. Warm-up time and print speed may vary depending on the operating environment. ©2015 TOSHIBA TEC CORPORATION All rights reserved.

TOSHIBA

Toshiba Tec (Thailand) Co., Ltd. (0105547146144)

No.43, Thai CC Tower, Room 164 -166, 16th Floor South Sathorn Road, annawa, Sathorn,

Bangkok 10120 Thailand.

Tel:+603-55687788 Service:+603-55687699 Fax:+603-55687700

Website: www.toshibatec.co.th