

TOSHIBA

e-STUDIO2822AF

Size Does Not Matter.
Small but Reliable.



COPY



PRINT



A3



DUPLEX



COLOUR
SCAN



COPY
SPEED



TOGETHER
INFORMATION

A3 With A Small Footprint



A compact machine which supports up to A3 size paper, all packed in a small A4 sized footprint.

Low Total Cost of Ownership (TCO)

Due to its size and functionality, this series offers a low total cost of ownership (TCO) as when compared with similar footprint products!



Reliable and Durable

No matter the environment, this series continually performs at its best so that productivity will never be compromised.



Special Media Print

Forms and labels can be printed for shipments, as well as waterproof paper printing capabilities to help in and around the workplace!



SPECIFICATION for		e-STUDIO2822AF
GENERAL		
Copying/Printing Process		Indirect electrostatic photographic method
Print & Copy Speed		28ppm (A4 size), 14ppm (A3 size via Bypass)/28cpm (A4 size)
Warm-up Time		Approx. 18 seconds
Paper Size & Weight		Drawer: A4 (64 - 80gsm) Stack Feed Bypass: A3/A5-R (52 - 216gsm)
Paper Capacity		Drawer: 250 sheets Stack Feed Bypass: 50 sheets
Max. Paper Capacity		300 sheets
Paper Exit		Face down/Inner exit (100 sheets)
Processor		Cortex A8 500MHz
Memory		512MB
Dimensions		W390 x D540 x H505 (mm)
Control Panel		LCD - W45 x H27 (mm) with Back light and Key top
Weight (Approx.)		28.5kg
Power Consumption		1.5kW (220-240V)
Operation Noise		64.75dB(A)
Special Features		Auto Power Save, Auto Sleep Mode, Energy Saver
COPY		
Max. Original Size		A3 (A4 on platen glass)
Resolution		2400dpi x 600dpi (with smoothing)
Multiple Copy Qty		1-999/Ten key input
First Copy		Less than 6.4 seconds (A4 size from 1st drawer, 100%)
Zoom		25% to 400% (1% Increment)
Copy Mode		Text, Text/Photo (Default), Photo, Background Erase
Image Density Control		Automatic/Manual (9 Steps)
PRINT		
Resolution		2400dpi x 600dpi (with smoothing), 600dpi x 600dpi (1 bit)
Page Description Language		PCL6 (PCL XL), PCL5e, PCL5c
Operating Systems		Windows 7 SP1 (32/64 bit)(Recommended) Windows 8.1 (32/64 bit) Windows 10 Redstone 5 Windows Server 2008 SP2 (32/64 bit)/R2 SP1 (64 bit) Windows Server 2012/R2 (64 bit) Windows Server 2016
Interface		Mac OS 10.11, 10.12, 10.13, 10.14 Linux / Redhat Enterprise 5.10.x, 6.5.x, 7.4X / Fedora Version 27 / Open SuSE Version 42.3, Bharat Operating System 6.x
Network Protocol		RJ45/USB 2.0
Print Protocol		TCP/IP (IP v4/IP v6) NetBIOS over TCP/IP
Print Function		LPR/LPD, Port 9100 (bi-directional), IPP ver1.1
Mobile Print		Toner Save Mode, Watermark, Multiple Pages Per Sheet, USB Direct Printing
Mobile Print		App (eBPC Entry), USB Connection
SCAN		
Resolution		600 x 600dpi
Scan Speed		Up to 25spm (with RADF)
Scan Modes		B&W, Greyscale, Colour
File Formats		B&W: TIFF-Multi/Single page, PDF-Multi/Single-Page Greyscale : JPEG, TIFF-Multi/Single page, PDF-Multi/Single Page Colour: JPEG, TIFF-Multi/Single page, PDF-Multi/Single Page
Scan Agent		Scan to USB/Mobile, Scan to File (SMB/FTP), Scan to Email
Mobile Scan		App (eBPC Entry), USB Connection
FAX		
Compatibility		ECM, Super G3, G3
Data Compression Method		JBIG, MMR, MR, MH
Modem Speed		33.6kbps -- 2.4Kbps (Auto fallback)
Transmission Speed		Approx. 3 sec.
Broadcast Transmission		Max. 256 jobs, 220 destinations/job, Max. 384 pages/file
OPTIONS		
Wireless LAN Module	GN-1160/C	✓
Harness Kit for Coin Controller	GG-1131	✓
Front Cover Customisation Kit	KK-2505	✓
Desk	MH-2505	✓

Distributed by

TOSHIBA

Toshiba Tec (Thailand) Co., Ltd. (0105547146144)

No.43, Thai CC Tower, Room 164 -166, 16th Floor
South Sathorn Road, Yannawa, Sathorn,
Bangkok 10120 Thailand.

Tel : +603-5568 7788 Service : +603-5568 7699 Fax : +603-5568 7700
Website : www.toshibatec.co.th

Microsoft and Windows® are registered trademarks of Microsoft Corporation in the United States and/or other countries. All other brand and/or product names are trademarks of their respective owners. This brochure was compiled based on information that was accurate prior to product launch. Product design and specifications are subject to change without notice. The colour(s) of the actual product may vary from the colour(s) shown in this brochure. No part of this material may be used or reproduced in any manner whatsoever without permission. 1GB is equivalent to 1 billion bytes. Warm-up time and print speed may vary depending on the operating environment. ©2015 TOSHIBA TEC CORPORATION All rights reserved.