TOSHIBA

e-STUDIO2822AF

Size Does Not Matter.
Small but Reliable.

COPY | PRINT | A3 | DUPLEX | COLOUR SCAN | 28 BW CPM COPY SPEED

TOGETHER INFORMATION™

A3 With A Small Footprint

A3 A4

A compact machine which supports up to A3 size paper, all packed in a small A4 sized footprint.

Low Total Cost of Ownership (TCO)

Due to its size and functionality, this series offers a low total cost of ownership (TCO) as when compared with similar footprint products!

Reliable and Durable

No matter the environment, this series continually performs at its best so that productivity will never be compromised.

Special Media Print

Forms and labels can be printed for shipments, as well as waterproof paper printing capabilities to help in and around the workplace!

SPECIFICATION for	e-STUDIO2822AF
GENERAL	
Copying/Printing Process	Indirect electrostatic photographic method
Print & Copy Speed	28ppm (A4 size), 14ppm (A3 size via Bypass)/28cpm (A4 size)
Warm-up Time	Approx. 18 seconds
Paper Size & Weight	Drawer: A4 (64 - 80gsm) Stack Feed Bypass: A3/A5-R (52 - 216gsm)
Paper Capacity	Drawer: 250 sheets Stack Feed Bypass: 50 sheets
Max. Paper Capacity	300 sheets
Paper Exit	Face down/Inner exit (100 sheets)
Processor	Cortex A8 500MHz
Memory	512MB
Dimensions	W390 x D540 x H505 (mm)
Control Panel	LCD - W45 x H27 (mm) with Back light and Key top
Weight (Approx.)	28.5kg
Power Consumption	1.5kW (220-240V)
Operation Noise	64.75dB[A]
Special Features	Auto Power Save, Auto Sleep Mode, Energy Saver
COPY	
Max. Original Size	A3 (A4 on platen glass)
Resolution	2400dpi x 600dpi (with smoothing)
Multiple Copy Qty	1-999/Ten key input
First Copy	Less than 6.4 seconds (A4 size from 1st drawer, 100%)
Zoom	25% to 400% (1% Increment)
Copy Mode	Text, Text/Photo (Default), Photo, Background Erase
Image Density Control	Automatic/Manual (9 Steps)
PRINT	
Resolution	2400dpi x 600dpi (with smoothing), 600dpi x 600dpi (1 bit)
Page Description Language	PCL6 (PCL XL), PCL5e, PCL5c
Operating Systems	Windows 7 SP1 (32/64 bit)(Recommended) Windows 8.1 (32/64 bit) Windows 10 Redstone 5 Windows Server 2008 SP2 (32/64 bit)/R2 SP1 (64 bit) Windows Server 2012/R2 (64 bit) Windows Server 2016
	Mac OS 10.11, 10.12, 10.13, 10.14 Linux / Redhat Enterprise 5.10.x, 6.5.x, 7.4X / Fedora Version 27 / Open SuSE Version 42.3, Bharat Operating System 6.x
Interface	RJ45/USB 2.0
Network Protocol	TCP/IP (IP v4/IP v6) NetBIOS over TCP/IP
Print Protocol	LPR/LPD, Port 9100 (bi-directional), IPP ver1.1
Print Function	Toner Save Mode, Watermark, Multiple Pages Per Sheet, USB Direct Printing
Mobile Print	App (eBPC Entry), USB Connection
SCAN	
Resolution	600 x 600dpi
Scan Speed	Up to 25spm (with RADF)
Scan Modes	B&W, Greyscale, Colour
File Formats	B&W: TIFF-Multi/Single page, PDF-Multi/Single-Page Greyscale : JPEG, TIFF-Multi/Single page, PDF-Multi/Single Page Colour: JPEG, TIFF-Multi/Single page, PDF-Multi/Single Page
Scan Agent	Scan to USB/Mobile, Scan to File (SMB/FTP), Scan to Email
Mobile Scan	App (eBPC Entry), USB Connection
FAX	
Compatibility	ECM, Super G3, G3
Data Compression Method	JBIG, MMR, MR, MH
Modem Speed	33.6kbps -- 2.4Kbps (Auto Fallback)
Transmission Speed	Approx. 3 sec.
Broadcast Transmission	Max. 256 jobs, 220 destinations/job, Max. 384 pages/file

OPTIONS		
Wireless LAN Module	GN-1160/C	✓
Harness Kit for Coin Controller	GQ-1131	✓
Front Cover Customisation Kit	KK-2505	✓
Desk	MH-2505	✓

For more information please contact us:

Toshiba Tec (Thailand) Co., Ltd. (0105547146144)

No. 43, Thai CC Tower, Room 164-166, 16th Floor,
South Sathorn Road, Yannawa, Sathorn,
Bangkok 101020 Thailand.

Tel : +662-672-3728 Service : +662-672-3728
Fax : +662-672-3730 Website : www.toshibatec.co.th

Microsoft and Windows® are registered trademarks of Microsoft Corporation in the United States and or other countries. All other brand and/or product names are trademarks of their respective owners. This brochure was compiled based on information that was accurate prior to product launch. Product design and specifications are subject to change without notice. The colour(s) of the actual product may vary from the colour(s) shown in this brochure. No part of this material may be used or reproduced in any manner whatsoever without permission. 1GB is equivalent to 1 billion bytes. Warm-up time and print speed may vary depending on the operating environment.
©2015 TOSHIBA TEC CORPORATION All rights reserved.

Toshiba Tec Group Philosophy

Creating with You